

**PREMIUM**  
**TRANSMISSION OIL**  
**TRUCKS & COMMERCIAL VEHICLES**



**QUALITY PERFORMANCE**

**MANUFACTURED IN BELGIUM**



**75W90 GEAR S**  
**FULLY SYNTHETIC**

**PERFORMANCE LEVEL**

API: GL-4	MAN: 342 M-3
API: GL-5	MB: 235.8
API: MT-1	MIL: PRF-2105E
ARVIN MERITOR: 0-76-N	RENAULT: B0032/3 Annex 3
DAF: GL5/MIL-PRF-2105E	SAE: J 2360
IVECO: MIL-PRF-2105E	SCANIA: STO 1
MACK: GO-J	ZF: TE-ML 02B
MAN: 341 E-3	ZF: TE-ML 05B
MAN: 341 Z-2	ZF: TE-ML 07A

**APPLICATIONS**

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.) of trucks and four-wheel drive vehicles.

**AVAILABLE SIZE**



**CHARACTERISTICS/SPECS**

**UNIT**

**AVERAGE VALUE**

Density at 15 °C	kg/l	0.869
Viscosity 40 °C	mm <sup>2</sup> /s	101.00
Viscosity 100 °C	mm <sup>2</sup> /s	15.40
Viscosity Index		161.00
Flash Point COC	°C	202.00
Pour Point	°C	-50.00
Total Base Number	mgKOH/g	2.10